

TJ Motor Leads™

TJ motor leads are designed for integration with submersible pumps and motors from select manufacturers, providing a direct, uninterrupted electrical connection between the motor and the control system. It features **ethylene tetrafluoroethylene (ETFE) insulation and an ETFE jacket**, making it **extremely resistant to high temperatures, chemicals, and abrasion**, with a **150°C** rating. The sleeve and jam nut are made of stainless steel. This design eliminates the need for field splicing.

Custom lead lengths are available, subject to National Electric Code (NEC) ampacity regulations for conductors in free air or submerged environments. In certain configurations, the ground conductor may need to be removed from the plug and externally connected via a ring terminal to the pump/motor studs or a dedicated grounding lug, if present on the motor.

For precise sizing and compatibility information, it is recommended to consult with sales or technical support.

Materials & Construction

AWG:	#12
Conductor:	19 STR Copper
Insulation:	FEP Fluoropolymer (ETFE)
Overall Jacket:	FEP Fluoropolymer (ETFE)
Sleeve:	316 Stainless Steel
Jam-nut:	316 Stainless Steel (if applicable)
Bushing:	Viton or Nitrile
Potting:	Epoxy (chemically resistant)

Applications

- ◆ Industrial
- ◆ Environmental
- ◆ Remediation
- ◆ PFAS
- ◆ Landfill / Leachate
- ◆ Sampling
- ◆ Oil & Gas

Options

- ◆ Artesian Adder
- ◆ Strip-back
- ◆ Ground out



*Not to scale.



Dimensions

AWG (+ ground)	# of Conductors	OD (in)	Weight lb/1000'	Temp °C
12	2	0.295"x0.593"	119	90 wet / 150 ; 600V
12	3	0.300"x0.745"	156	

Motor Compatibility

FRANKLIN	GOULD'S	GRUNDFOS	FARADYNE	HITACHI
All 4", 6", 8" Encapsulated Motors	<ul style="list-style-type: none"> ◆ All 4" Motors ◆ 6" M-Series Motors 	<ul style="list-style-type: none"> ◆ 4" MS402 & MS4000 Motors ◆ 3" MSE3 Motors (SQE/RF3) <p>*not compatible with MS4000C Motors*</p>	<ul style="list-style-type: none"> ◆ 4" FM-Series 	6" Canned Type Motors