


# TECHNICAL DATA

## DIMENSIONS AND WEIGHTS

MODEL NO.	HP	MOTOR SIZE	DISCH. SIZE	DIMENSIONS IN INCHES					APPROX. SHIP WT.
				A	B	C	D	E	
16S05-5PETF	1/2	4"	1 1/4" NPT	19.7	9.5	10.2	3.8	3.9	27
16S07-8PETF	3/4	4"	1 1/4" NPT	23.4	10.7	12.7	3.8	3.9	29
16S10-10PETF	1	4"	1 1/4" NPT	26.2	11.8	14.4	3.8	3.9	32
16S15-14PETF	1 1/2	4"	1 1/4" NPT	32.8	15.1	17.7	3.8	3.9	36
16S20-18PETF	2	4"	1 1/4" NPT	36.0	15.1	20.9	3.8	3.9	40
16S30-24PETF	3	4"	1 1/4" NPT	46.5	20.6	25.9	3.8	3.9	64
16S50-38PETF	5	4"	1 1/4" NPT	61.1	23.6	37.5	3.8	3.9	94
16S75-56DS*PETF	7 1/2	6"	1 1/4" MPT	93.0	24.2	68.8	5.4	4.6	220
16S100-75DS*PETF	10	6"	1 1/4" MPT	109.9	25.4	84.5	5.4	4.6	245

NOTES: All models suitable for use in 4" wells, unless otherwise noted. Weights include pump end with motor in lbs.

\* Built into sleeve 1 1/4" MPT discharge, 6" min. well dia.



## MATERIALS OF CONSTRUCTION

COMPONENT	SPLINED SHAFT (5-24 Stgs.)	CYLINDRICAL SHAFT (38 Stgs.)	DEEP SET (56-75 Stgs.)
Check Valve Housing	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel
Check Valve	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel
Diffuser Chamber	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel
Impeller	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel
Suction Interconnector	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel
Inlet Screen	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel
Pump Shaft	304 Stainless Steel	431 Stainless Steel	431 Stainless Steel
Straps	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel
Cable Guard	304 Stainless Steel	304 Stainless Steel	304 Stainless Steel
Priming Inducer	304 Stainless Steel	316 Stainless Steel	316 Stainless Steel
Coupling	329/420/431 Stainless Steel	329/420/431 Stainless Steel	329/416 Stainless Steel**
Check Valve Seat	NBR/304 Stainless Steel	NBR/316 Stainless Steel	NBR/316 Stainless Steel
Top Bearing	Teflon®/304 Stainless Steel	Teflon®/316 Stainless Steel	Teflon/316 Stainless Steel
Impeller Seal Ring	Teflon®	Teflon®	Teflon®
Intermediate Bearings	Teflon®	304 Stainless Steel	Teflon/316 Stainless Steel
Shaft Washer	Not Required	LC P (Vectra®)	LC P (Vectra®)
Split Cone	Not Required	304 Stainless Steel	304 Stainless Steel
Split Cone Nut	Not Required	316 Stainless Steel	304 Stainless Steel
Sleeve	Not Required	Not Required	316 Stainless Steel
Sleeve Flange	Not Required	Not Required	Zincless Bronze*
Coupling Key	Not Required	Not Required	302/304 Stainless Steel**

NOTES: Specifications are subject to change without notice. Valox® is a registered trademark of General Electric Co.

Vectra® is a registered trademark of Hoechst Calanese Corporation. Ryton® is a registered trademark of Phillips 66. Available in 316SS configuration.

\*\* If using 4" non-standard motors, refer to 329/420/431 Stainless Steel for coupling. A coupling key is not required.

**PUMPSOK**  
Real. Friendly. Experts.™

Pumps of Oklahoma Inc.  
1220 N.W. 3rd Street • Oklahoma City, OK 73106  
Toll-free 1.800.669.3574 • Phone: 405.235.2695  
Fax: 405.235.9897 • Web: pumpsok.com